



HIGHLY FLEXIBLE SKID PROOF HEAT SHRINKABLE TUBE

SHRINK RATIO: 2:1

SKID RESISTANT

RoHS

SKID-100 is a highly flexible, skid resistant, environment friendly, heat shrinkable tube.

Bright colors enhance the appearance of finished products such as handle bars, fishing tackle, exercise equipment, etc. This product is designed to enhance friction when being held. Order **SKID-125** with bright colored stripes for a little variety in the appearance fishing tackle



SKID-100 Applications

Comfortable Grip

Skid Resistant

Bright Colors for Product Identification

Offers Protection against Moisture

Fast Shrinkage for Easy Application

Characteristics

Operating Temperature: -55° to 105° Celsius

Shrink Temperature: Start at 70° C; Completely Shrunk 110° C

Shrink Ratio: 2:1

Colors: Black, Red, Yellow, Green, Blue (Other Colors Available per Request) Also Available with Cool Stripes

Specifications

Gamma Part No.	As Supplied		After Recovery		Standard Packaging
	W/ Size ID (mm)	Wall Thickness (mm)	Max ID (mm)	ID (mm)	4FT Lngth
SKID-100-15mm	15	0.45	8	0.85	200'
SKID-100-20mm	20	0.50	11	0.90	200'
SKID-100-22mm	22	0.50	12.5	0.90	200'
SKID-100-25mm	25	0.50	14.5	1.00	100'
SKID-100-28mm	28	0.50	15.5	1.00	100'
SKID-100-30mm	30	0.60	17.5	1.20	100'
SKID-100-35mm	35	0.60	20	1.20	50'
SKID-100-40mm	40	0.60	23	1.20	50'
SKID-100-45mm	45	0.65	25	1.25	50'
SKID-100-50mm	50	0.65	28	1.25	50'

Color Code: 0=BLK, 1=BRN, 2=RED, 3=ORN, 4=YLW, 5=GRN, 6=BLU, 7=VIO, 8=GRY, 9=WHT, X=CLR

P/N Example: SKID-100-25mm-0 = Black 25mm Black Skid Resistant Tubing

P/N Example: SKID-125-25mm-0/2 = Black w/ Red Stripes 25mm Skid Resistant Tubing

Property of Gamma Electronics

www.gammaelectronics.net