

Gamma's EPDM cold shrink is specially formulated pre-expanded rubber shrink tube that does not require heat to shrink. It is supplied expanded over an easily removable plastic cylindrical core. When the plastic cord is pulled, it allows the rubber tubing to shrink and rapidly seal and protect the connector, while gripping tightly around the cable.

These cold shrink kits are a safe, simple and reliable method to seal coaxial connections.

EPDM cold shrink kits are ideal for wireless communication towers and any other exposed coax interface. They are applied without heat or flame and installed without tools. Once installed correctly, the connection is weatherproof and protected against dust and dirt that may find its way into your connection.



### Features

- Simple installation, requires only workman's hands
- No torch or heat source required for installation
- Good thermal stability
- Seals tight, retains its resiliency and compression even after prolonged years of environmental exposure
- Waterproof
- Resistant to fungus, acids, alkalis, ozone and ultraviolet light
- Accommodates a wide range of cables
- Excellent electrical properties while wet
- Improved tough rubber formulation to withstand rough backfilling

## Specifications

Gamma's Cold Shrink Kit contains EPDM rubber sleeves that are applied without a heat gun or torch. It's an open-ended, tubular rubber sleeve that are factory expanded and assembled onto a removable plastic core. They are supplied for field installation in the pre-stretched condition.

## Ordering Information

Part Number	Starting ID	Recovered Length (mm)	Recovered ID Range (mm)	Color
EPDM-8320-152	Ø 20	152	8-15	Black
EPDM-8320-205	Ø 20	205	8-15	Black
EPDM-8325-152	Ø 25	152	10-20	Black
EPDM-8325-205	Ø 25	205	10-20	Black
EPDM-8335-152	Ø 35	152	12.5-30	Black
EPDM-8335-205	Ø 35	205	12.5-30	Black
EPDM-8340-152	Ø 40	152	14-33	Black
EPDM-8340-205	Ø 40	205	14-33	Black
EPDM-8353-152	Ø 53	152	19-46	Black
EPDM-8353-205	Ø 53	205	19-46	Black
EPDM-8360-152	Ø 60	152	20.5-51	Black
EPDM-8360-205	Ø 60	205	20.5-51	Black
EPDM-8370-152	Ø 70	152	24.5-61	Black
EPDM-8370-205	Ø 70	205	24.5-61	Black
EPDM-8380-152	Ø 80	152	27.4-70	Black
EPDM-8380-205	Ø 80	205	27.4-70	Black
EPDM-83104-152	Ø 104	152	42.5-94	Black
EPDM-83104-205	Ø 104	205	42.5-94	Black
EPDM-83125-152	Ø 125	152	46-114	Black
EPDM-83125-205	Ø 125	205	46-114	Black
EPDM-83150-152	Ø 150	152	55-135	Black
EPDM-83150-205	Ø 150	205	55-135	Black



## EPDM Cold Shrink

RoHS : compliant with EU RoHS Directive (2005/95/EC)

“RoHS Compliant 2005/95/EC” means that the product or part (“Product”) does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under RoHS. This information represents Gamma Electronic’s knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to Gamma Electronic’s.

**Property of Gamma Electronics Inc.**

2818 Metropolitan Place, Suite A  
Pomona, CA 91767  
[www.gammaelectronics.net](http://www.gammaelectronics.net)